

Material Safety Data Sheet

Cyberbond LLC

401 N. Raddant Rd. Batavia, IL 60510
Tel: 630-761-8900; Fax: 630-761-8989
Emergency Tel: 800-535-5053

1- Chemical Product and Company Identification:

Product Name: **Apollo Boost 6010**

Product Type: Primer

Date revised: 8-3-99

2- Composition/Information on Ingredients:

<u>Hazardous Component</u>	<u>CAS Number</u>	<u>%</u>	
Ethyl Alcohol	64-17-5	45-55	
Ethyl Acetate	141-78-6	35-45	
Active Ingredient	Trade Secret	1-5	
<u>Exposure Limits (TWA)</u>	<u>ACGIH (TLV)</u>	<u>OSHA (PEL)</u>	<u>OTHER</u>
Ethyl Alcohol	1000 ppm	1000 ppm	(NIOSH)1000 ppm
Ethyl Acetate	750 ppm	750 ppm	none

3- Hazards Identification:

Toxicity: Possible eye and respiratory irritant. Narcotic at high concentrations. Prolonged inhalation may cause headaches. Moderately toxic by ingestion. Liquid may dry out skin.

Primary routes of Entry: Inhalation, Ingestion, contact.

Signs of exposure: Vapors irritate eyes, nose, and throat. Liquid is an eye irritant and may irritate skin.

4- First Aid Measures:

Ingestion: Give water to dilute. Do not induce vomiting. Keep individual calm and seek medical attention.
Inhalation: Remove to fresh air. If symptoms persist, obtain medical attention.
Skin contact: Wash in warm water.
Eye contact: Flush with warm water. Seek medical attention.

5- Fire Fighting Measures:

Flash Point: 20-30°F, Tag Closed Cup
Extinguishing Media: Foam, Dry Chemical or Carbon Dioxide
Unusual Fire or Explosion Hazards: None.
Special Fire Fighting Procedures: N/A.
Hazardous Products Formed by Fire or Thermal decomposition: Irritating Organic Vapors

6-Accidental Release Measures

Steps to be taken in case of spill or leak: Avoid flame and sparks. Maintain adequate ventilation. Soak up in an inert Absorbent and store in a closed container until disposal.

7- Handling and Storage:

Safe storage: Store away from flame and sparks.
Handling: Keep container tightly closed. Avoid contact with skin. Avoid breathing vapors. Do not use around heat, sparks, or open flame .

Material Safety Data Sheet

Cyberbond LLC

401 N. Raddant Rd. Batavia, IL 60510
Tel: 630-761-8900; Fax: 630-761-8989
Emergency Tel: 800-535-5053

Apollo Boost 6010

8- Protective Equipment:

Ventilation:	Local exhaust ventilation recommended to maintain vapor level below TLV.
Respiratory protection:	Not applicable with good local exhaust.
Skin:	Polyethylene or non reactive gloves.
Eye protection:	Safety glasses or goggles with side shields.

9- Physical and Chemical Properties:

Appearance:	Clear liquid
Odor:	Sharp, pungent
Boiling Point:	133°F
Vapor Pressure:	181.7mmHg @68°F
Vapor Density:	n/a
Evaporation rate:	Slower than ethyl ether
Specific Gravity:	.877 @ 77°F
Solubility in water:	Miscible
Volatile Organic Compound: (EPA Method 24)	99.9% 680 grams per liter

10- Stability and Reactivity

Stability:	Stable
Hazardous Polymerization:	Will not occur
Incompatibility:	Avoid contact with strong oxidizing agents.

11- Toxicological Information

See Section 3

12-Ecological Information

No Data

13- Disposal Considerations:

Disposal procedures: Incinerate or dispose of in an approved landfill in accordance with local and EPA regulations.

14- Transportation Information:

Domestic Ground Transport:	
Proper shipping name:	Consumer Commodity (not more than one liter) Compounds, Cleaning, Liquid (more than one liter)
Hazard class or division:	ORM-D (Not more than one liter) Class 3, Packing Group II (More than one liter)
Identification number:	None (Not more than one liter) NA 1993 (More than one liter)
Marine pollutant:	No

Material Safety Data Sheet

Cyberbond LLC

401 N. Raddant Rd. Batavia, IL 60510
Tel: 630-761-8900; Fax: 630-761-8989
Emergency Tel: 800-535-5053

Apollo Boost 6010

15- Regulatory Information

US Federal Regulations

TSCA (Toxic Substances Control Act) Status

TSCA (United States) The intentional ingredients of this product are listed.

CERCLA RQ (Reportable Quantity) – 40 CFR 302.4 (a)

<u>Component</u>	<u>RQ (lbs.)</u>
Ethyl Acetate	5000
Ethyl Alcohol	5000

SARA 302 Components – 40 CFR 355 Appendix A: NONE

Section 311/312 Hazard Class – 40 CFR 370.2

Immediate(x) Delayed(x) Fire(x) Reactive() Sudden Release of Pressure()

SARA 313 Components – 40 CFR 372.65: NONE

International Regulations

Inventory Status: Not Determined

State and Local Regulations

CA Proposition 65: The following statement is made in order to comply with the California Safe Drinking Water and Toxic Enforcement Act of 1986: This product contains the following substance known to the state of California to cause reproductive harm; ETHYL ALCOHOL

16- Other Information

<u>Hazard</u>	<u>NFPA Hazard Code®</u>	<u>HMIS Hazard Code®</u>
Health	1	1
Fire	3	3
Reactivity	0	0
Specific Hazard	Not Applicable	Personal protection: See Section 8

NFPA is a registered trademark of the National Fire Protection Association
HMIS is a registered trademark of the National Paint and Coatings Association

Prepared by: Fred W Cain
Company: Cyberbond LLC
Revision Date: 3-Aug-1999